

CloudEngine 7800 Series Data Center Switches



CloudEngine 7800 Series Data Center Switches

Product Overview

Huawei CloudEngine 7800 series (CE7800 for short) switches are next-generation 40G Ethernet switches designed for data centers and high-end campus networks, providing high-performance, high-density 40GE ports, and low latency. The CE7800 has an advanced hardware architecture with 40GE QSFP+ ports.

Using the Huawei VRP8 software platform, CE7800 switches provide extensive data center service features and high stacking capability. In addition, the airflow direction (front-to-back or back-to-front) can be changed. CE7800 switches can work with CE12800/8800/6800/5800 switches to build an elastic, virtualized, high-quality fabric that meets the requirements of cloud-computing data centers. CE7800 switches can function as core or aggregation switches on data center networks to help enterprises and carriers build a scalable data center network platform in the cloud computing era. They can also be used as aggregation or core switches for enterprise campus networks.

Product Appearance

The CE7800 comes in one model.



Product Characteristics

High-density 40GE Access

- The CE7800 provides 2.56 Tbit/s switching capacity in a 1 U ToR, 1,440 mpps forwarding performance, and supports L2/L3 line-rate forwarding.
- The CE7800 provides a maximum of 32*40GE QSFP+ ports, and can function as the core or aggregation switch on a data center or campus network.
- The QSFP+ port can be used as four 10GE SFP+ ports, providing a flexible network. CE7800 switches can work with CE12800/6800/5800 switches to build a non-blocking network platform.

Highly Reliable, High-Performance Stacking

- The industry's first 16-member stack system
 - » A stack system of 16 member switches has a maximum of 512*40GE access ports that provide high-density server access in a data center.
 - » Multiple switches in a stack system are virtualized into one logical device, making it possible to build a scalable, easy-to-manage data center network platform.

- » A stack system separates the control plane from the data plane. This eliminates the risk of single points of failure and greatly improves system reliability.
- Long-distance stacking
 - » The CE7800 can use service ports as stack ports. A stack system can be established with switches in the same rack or different racks, and even over long distances.
 - » Service and stack bandwidths can be allocated based on the network's scale so that network resources can be used more efficiently.

Vertical Virtualization Simplifies Management

- The CE7800 supports Super Virtual Fabric (SVF), which can virtualize multiple physical switches of the same or different types into one logical switch to simplify network management and improve reliability.
- SVF implements vertical extension of heterogeneous switches and virtualizes multiple leaf switches into remote cards of the spine switch, making it easier to install cables in equipment rooms and manage devices. The CE7800 functions as the spine switch.
- Huawei's SVF is the first in the industry to implement local forwarding on leaf switches. When horizontal traffic is the mainstream traffic in a data center, SVF improves forwarding efficiency and reduces network delay.

Inter-device Link Aggregation, High Efficiency and Reliability

- The CE7800 supports multichassis link aggregation group (M-LAG), which enables links of multiple switches to aggregate into one to implement device-level link backup.
- Switches in an M-LAG system all work in active state to share traffic and back up each other, enhancing system reliability.
- Switches in an M-LAG system can be upgraded independently. During the upgrade, other switches in the system take over traffic forwarding to ensure uninterrupted services.
- M-LAG supports dual-homing to Ethernet, TRILL, VXLAN, and IP networks, allowing for flexible networking.
- With the industry's most comprehensive inter-device link aggregation technology, the device networking coupling relationship evolves from stacking at the control plane to the use of M-LAG and then finally to coupling-free M-LAG Lite. This achieves active-active server access and zero interruption of services when upgrading switches.

Large-Scale Routing Bridge, On-Demand Scaling

- The CE7800 supports the IETF Transparent Interconnection of Lots of Links (TRILL) protocol. A TRILL network can contain more than 500 nodes, enabling flexible service deployments and large-scale Virtual Machine (VM) migrations.
- The TRILL protocol uses a routing mechanism similar to IS-IS and sets a limited time to live (TTL) value in packets to prevent Layer 2 loops. This significantly improves network stability and speeds up network convergence.
- On a TRILL network, all data flows are forwarded quickly using Shortest Path First (SPF) and Equal-cost Multi-path (ECMP) routing. SPF and ECMP avoid the suboptimal path selection problem in STP and increase link bandwidth efficiency to 100 percent.

- The CE7800 supports TRILL-based Layer 2 equal-cost paths, greatly improving links' load balancing capabilities. The network has a fat-tree architecture that enhances expansion.

Converged Enhanced Ethernet, Allowing for Data, Storage, and Computing Traffic on One Network

- The CE7800 supports Fibre Channel over Ethernet (FCoE), which permits storage, data, and computing services to be transmitted on one network, reducing the costs of network construction and maintenance.
- The CE7800 supports centralized FCoE/FC gateway deployment, which makes network O&M simpler.
- The CE7800 series switches support multiple data center features: Priority-based Flow Control (PFC), Enhanced Transmission Selection (ETS) and Data Center Bridging eXchange (DCBX). These features ensure low latency and zero packet loss for FC storage and high-speed computing services.

Full Openness and Programmability, Flexible Customization

- The CE7800 uses the Open Programmability System (OPS) embedded in the VRP8 software platform to provide programmability at the control plane.
- The OPS provides open APIs. APIs can be integrated with mainstream cloud platforms (including commercial and open cloud platforms) and third-party controllers. The OPS enables services to be flexibly customized and provides automatic management.
- Users or third-party developers can use open APIs to develop and deploy specialized network management policies to implement extension of fast service functions, automatic deployment, and intelligent management. The OPS also implements automatic operation and maintenance, and reduces management costs.
- The CE7800 supports CE modules for Ansible, which enables unified provisioning of physical and virtual networks.
- CE7800 switches can seamlessly integrate with systems of F5, an industry-leading application delivery network provider, to build an active-active data center network.
- The OPS provides seamless integration of data center service and network in addition to a service-oriented, software-defined networking (SDN).

Hardware Overlay Gateway Achieves Fast Service Deployment

- The CE7800 can work with a mainstream virtualization platform. As the high-performance, hardware gateway of an overlay network (VXLAN), the CE7800 can support more than 16 million tenants.
- The CE7800 can connect to a cloud platform through an open API to provide unified management of software and hardware networks.
- The hardware gateway deployment enables fast service deployment without changing the customer network, providing investment protection.
- The CE7800 supports Border Gateway Protocol - Ethernet VPN (BGP-EVPN), which can run as the VXLAN control plane to simplify VXLAN configuration within and between data centers.

Zero Touch Provisioning, Automatic O&M

- The CE7800 supports Zero Touch Provisioning (ZTP). ZTP enables the CE7800 to automatically obtain and load version files from a USB flash drive or file server, freeing network engineers from onsite configuration or deployment. ZTP reduces labor costs and improves device deployment efficiency.
- ZTP provides built-in scripts for users through open APIs. Data center personnel can use the programming language they are familiar with, such as Python, to provide unified configuration of network devices.
- ZTP decouples configuration time of new devices from device quantity and area distribution, which improves service provisioning efficiency.

Intelligent O&M with the FabricInsight Solution

- The CE6870 provides proactive path detection on the entire network. It periodically checks sample flows to determine connectivity of all paths on the network and locates failure points, enabling you to know the network health in real time.
- The CE6870 supports visualization of all flows and congestion, improving service experience.

Flexible Airflow Design, High Energy Efficiency

- Flexible front-to-back/back-to-front airflow design
 - » The CE7800 uses a front-to-back/back-to-front airflow design that isolates cold air channels from hot air channels. This design meets heat dissipation requirements in data center equipment rooms.
 - » Air can flow from front to back, or back to front when different fans and power modules are used.
 - » Redundant power modules and fans can be configured to ensure uninterrupted service transmission.
- Innovative energy-saving technology
 - » The CE7800 has energy-saving chips and can measure system power consumption in real time. Fan speed can be adjusted dynamically based on system consumption. These energy-saving technologies reduce O&M costs and contribute to a greener data center.

Clear Indicators, Simple Maintenance

- Clear indicators
 - » Port indicators clearly show port status and port speeds. The 40GE port indicators can show the state of all the 10GE ports derived from the 40GE ports.
 - » State and stack indicators on both the front and rear panels enable operators to maintain the switch from either side.
 - » The CE7800 supports remote positioning. Operators can turn on remote positioning indicators on the switches they want to maintain, so that they can find switches easily in an equipment room full of devices.
- Simple maintenance
 - » The management port, fans, and power modules are on the front panel, which facilitates device maintenance.
 - » Data ports are located at the rear, facing servers. This simplifies cabling.

Product Specifications¹

Functions and Features

Item	CE7855-32Q-EI
Device virtualization	iStack ²
	SVF ³
	M-LAG
Network virtualization	TRILL
	VXLAN routing and bridging
	BGP-EVPN
	QinQ access VXLAN
Data center interconnect	VXLAN mapping, implementing interconnection between multiple DCI networks at Layer 2
SDN	Agile Controller
	VMware NSX
Network convergence	FCoE
	DCBX, PFC, ETS
Programmability	OPS
	CE modules for Ansible released on open source websites
Traffic analysis	NetStream
	sFlow
VLAN	Adding access, trunk, and hybrid interfaces to VLANs
	Default VLAN
	QinQ
	MUX VLAN
	GARP VLAN registration protocol(GVRP)
MAC address table	Dynamic learning and aging of MAC addresses
	Static, dynamic, and blackhole MAC address entries
	Packet filtering based on source MAC addresses
	MAC address limiting based on ports and VLANs

¹ This content is applicable only to regions outside mainland China. Huawei reserves the right to interpret this content

² For details about the configuration, please see: http://support.huawei.com/online/toolsweb/virtual/en/dc/stack_index.html?dcb

³ For details about the configuration, please see: http://support.huawei.com/online/toolsweb/virtual/en/dc/svf_index.html?dcb

Item	CE7855-32Q-EI
IP routing	IPv4 routing protocols, such as RIP, OSPF, BGP, and IS-IS
	IPv6 routing protocols, such as RIPng, OSPFv3, IS-ISv6, and BGP4+
IPv6	IPv6 Neighbor Discovery (ND)
	IPv6 VXLAN over IPv4
	Path MTU Discovery (PMTU)
	TCP6, ping IPv6, tracer IPv6, socket IPv6, UDP6, and Raw IP6
Multicast	IGMP, PIM-SM, PIM-DM, MSDP, and MBGP
	IGMP snooping
	Fast leaving of multicast member interfaces
	Multicast traffic suppression
	Multicast VLAN
	Multicast VXLAN
MPLS	MPLS
Reliability	LACP
	STP, RSTP, VBST, and MSTP
	BPDU protection, root protection, and loop protection
	Smart Link and multi-instance
	DLDP
	ERPS (G.8032)
	VRRP, VRRP load balancing, and BFD for VRRP
	BFD for BGP/IS-IS/OSPF/Static route
	BFD for VXLAN
O&M	Network-wide path detection
	Telemetry
	Statistics on the buffer microburst status
	VXLAN OAM: VXLAN ping, VXLAN tracer

Item	CE7855-32Q-EI
QoS	Traffic classification based on Layer 2 headers, Layer 3 protocols, Layer 4 protocols, and 802.1p priority
	Actions of ACL, CAR, re-marking, and scheduling
	Queue scheduling algorithms, including PQ, WRR, DRR, PQ+WRR, and PQ+DRR
	Congestion avoidance mechanisms, including WRED and tail drop
	Traffic shaping
Configuration and maintenance	Console, Telnet, and SSH terminals
	Network management protocols, such as SNMPv1/v2c/v3
	File upload and download through FTP and TFTP
	BootROM upgrade and remote upgrade
	802.3az Energy Efficient Ethernet (EEE)
	Hot patches
	User operation logs
Security and management	Zero Touch Provisioning (ZTP)
	802.1x authentication
	Command line authority control based on user levels, preventing unauthorized users from using commands
	DoS, ARP, and ICMP attack defenses
	Port isolation, port security, and sticky MAC
	Binding of the IP address, MAC address, interface number, and VLAN ID
	Authentication methods, including AAA, RADIUS, and HWTACACS
	Remote Network Monitoring (RMON)

Performance and Scalability

Item	CE7855-32Q-EI
Maximum number of MAC address entries	256K/128K
Maximum number of Forwarding routes (FIB IPv4/ IPv6)	128K
ARP table size	4096
Maximum number of VRF	48K
IPv6 ND(Neighbour Discovery) table size	8K
Maximum Number of multicast routes (Multicast FIB IPv4/IPv6)	64
Maximum VRRP groups	16K
Maximum number of ECMP paths	32
Maximum ACL number	ingress14750/egress 1000
Maximum Number of broadcast domains	4K
Maximum number of BDIF	15K
Maximum number of tunnel endpoints (VTEP)	288K
Maximum number of lag group	1024/512/256/128/64
Maximum number of links in a lag group	2/4/8/16/32
Maximum number of MSTP instance	64
VBST (Maximum number of VLANs where VBST can be configured)	500

NOTE

This specification may vary between different scenarios. Please contact Huawei for details.

Hardware Specifications

Item	CE7855-32Q-EI
Physical Features	Dimensions (W × D ×H ,mm)
	442*600*43.6
	Weight (kg)
	11.2
Physical Features	Switching capacity(Tbits/s)
	2.56
Physical Features	Forwarding performance(Mpps)
	1440
Ports	32 *40GE QSFP+

Item		CE7855-32Q-EI
Card	Number of card slot	1
	Card type	Fixed Switch
Management interface	Out-of-band management port	1*GE management interface
	Console port	1*RJ45 serial interface
	USB port	1
CPU	Main frequency(HZ)	1.5G
	Number of cores	4
Storage	RAM	4GB
	NOR Flash	16MB
	NAND Flash	1GB
System	System buffer	16MB
Power Supply System	Power modules	600 W AC
	Rated voltage range(V)	100 ~ 240 AC
	Maximum voltage range(V)	90 ~ 290 AC
	Maximum input current	100 V to 240 V 9 A
	Typical power	262W(100% traffic load, copper cable, normal temperature, dual power modules)
	Maximum power (W)	444
	Frequency (AC ,HZ)	50/60
Heat Dissipation	Heat dissipation mode	Air cooling
	Number of fans	2
	Heat dissipation airflow	Front-to-back or back-to-front airflow
	Maximum heat consumption (BTU/hr)	1516

Item		CE7855-32Q-EI
Environment specifications	Long-term operating temperature(℃)	0 to 40℃ (0-1800m) The temperature decreases by 1℃ each time the altitude increases by 220 m.
	Storage temperature(℃)	-40 to +70℃
	Relative humidity	5% to 95%
	Operating altitude (m)	Up to 5000
	Sound power at 27℃ (dBA)	Front-to-back airflow: < 64 Back-to-front airflow: < 65
	Sound power at 40℃ (dBA)	Front-to-back airflow: < 83 Back-to-front airflow: < 84
	Sound pressure at 27℃ (dBA)	Front-to-back airflow: 50 in average (maximum: 54) Back-to-front airflow: 51 in average (maximum: 55)
	Surge protection	AC power supply protection: 6 kV in common mode and 6 kV in differential mode
Reliability	MTBF (year)	49.81
	MTTR (hour)	1.81
	Availability	0.99999584354

NOTE

For detailed information of CloudEngine 7800 Platform hardware information, visit <https://support.huawei.com/enterprise/en/doc/EDOC1000019246?idPath=7919710%7C21782165%7C21782239%7C22318540%7C7597815>

Safety and Regulatory Compliance

The following table lists the safety and regulatory compliance of CE 7800.

Certification Category	Description
Safety	<ul style="list-style-type: none"> • EN 60950-1: 2006+A11: 2009+A1: 2010+A12: 2011 • EN 60825-1: 2007 • EN 60825-2: 2010 • UL 60950-1: 2007 2nd Edition • CSA C22.2 No.650: 2007 2nd Edition • IEC 60950-1: 2005+A1: 2009 • AS/NZS 60950-1: 2011 • GB4943: 2011

Certification Category	Description
Electromagnetic Compatibility (EMC)	<ul style="list-style-type: none"> • FCC 47CFR Part15 CLASS A • ETSI EN 300 386 V1.6.1: 2012 • ICES-003: 2012 CLASS A • CISPR 22: 2008 CLASS A • CISPR 24: 2010 • EN 55022: 2010 CLASS A • EN 55024: 2010 • AS/NZS CISPR 22: 2009 CLASS A • IEC 61000-3-2: 2005+A1: 2008+A2: 2009/EN 61000-3-2: 2006+A1: 2009+A2: 2009 • IEC 61000-3-3: 2008/EN 61000-3-3: 2008 • CNS 13438: 2006 CLASS A • VCCI V-4: 2012 CLASS A • VCCI V-3: 2012 CLASS A • EC Council Directive 2004/108/EC • GB9254
Environment	<ul style="list-style-type: none"> • 2002/95/EC, 2011/65/EU • 2002/96/EC, 2012/19/EU • EC NO.1907/2006 • ETSI EN 300 019-1-1 V2.1.4 • ETSI EN 300 019-1-2 V2.1.4 • ETSI EN 300 019-1-3 V2.3.2 • ETSI EN 300753 V1.2.1

NOTE

- EMC: electromagnetic compatibility
- CISPR: International Special Committee on Radio Interference
- EN: European Standard
- ETSI: European Telecommunications Standards Institute
- CFR: Code of Federal Regulations
- FCC: Federal Communication Commission
- IEC: International Electrotechnical Commission
- AS/NZS: Australian/New Zealand Standard
- VCCI: Voluntary Control Council for Interference
- UL: Underwriters Laboratories
- CSA: Canadian Standards Association
- IEEE: Institute of Electrical and Electronics Engineers
- RoHS: restriction of the use of certain hazardous substances
- REACH: Registration Evaluation Authorization and Restriction of Chemicals
- WEEE: Waste Electrical and Electronic Equipment

MIB and Standards Compliance

Supported MIBs

The following table lists the MIBs supported by CE 7800 series switches.

Category	MIB
Public MIB	<ul style="list-style-type: none"> • BRIDGE-MIB • BGP4-MIB • BRIDGE-MIB • DISMAN-PING-MIB • DISMAN-TRACEROUTE-MIB • ENTITY-MIB • IF-MIB • IP-FORWARD-MIB • IP-MIB • IPMCAST-MIB • IPv6-ICMP-MIB • IPv6-MIB • IPv6-TCP-MIB • IPv6-UDP-MIB • ISIS-MIB • LAG-MIB • LLDP-EXT-DOT1-MIB • LLDP-EXT-DOT3-MIB • LLDP-MIB • MAU-MIB • MGMD-STD-MIB • MPLS-FTN-STD-MIB • MPLS-L3VPN-STD-MIB • MPLS-LDP-GENERIC-STD-MIB • MPLS-LDP-STD-MIB • MPLS-LSR-STD-MIB • MSDP-MIB • NOTIFICATION-LOG-MIB • NQA-MIB • OSPF-MIB • OSPF-TRAP-MIB • OSPFV3-MIB • P-BRIDGE-MIB • PIM-BSR-MIB • PIM-STD-MIB • Q-BRIDGE-MIB • RADIUS-AUTH-CLIENT-MIB • RFC1213-MIB • RIPv2-MIB • RMON-MIB • SNMP-FRAMEWORK-MIB • SNMP-MPD-MIB • SNMP-NOTIFICATION-MIB • SNMP-PROXY-MIB • SNMP-TARGET-MIB • SNMP-USER-BASED-SM-MIB • SNMPv2-MIB • SNMP-VIEW-BASED-ACM-MIB • TCP-MIB • UDP-MIB • VRRP-MIB

Category	MIB
Huawei-proprietary MIB	<ul style="list-style-type: none"> • HUAWEI-AAA-MIB • HUAWEI-ACL-MIB • HUAWEI-ALARM-MIB • HUAWEI-BASE-TRAP-MIB • HUAWEI-BFD-MIB • HUAWEI-BGP-VPN-MIB • HUAWEI-BRAS-RADIUS-MIB • HUAWEI-CBQOS-MIB • HUAWEI-CE-PING-MIB • HUAWEI-CONFIG-MAN-MIB • HUAWEI-CPU-MIB • HUAWEI-DAD-MIB • HUAWEI-DATASYNC-MIB • HUAWEI-DEVICE-MIB • HUAWEI-DEVICE-EXT-MIB • HUAWEI-DHCPR-MIB • HUAWEI-DHCP-SNOOPING-MIB • HUAWEI-DHCPV6-SERVER-MIB • HUAWEI-DLDP-MIB • HUAWEI-ENERGYMNGT-MIB • HUAWEI-ENTITY-TRAP-MIB • HUAWEI-ENTITY-EXTENT-MIB • HUAWEI-ETHOAM-MIB • HUAWEI-ERPS-MIB • HUAWEI-ERRORDOWN-MIB • HUAWEI-ETHARP-MIB • HUAWEI-EVC-MIB • HUAWEI-FCOE-MIB • HUAWEI-FLASH-MAN-MIB • HUAWEI-FTP-MIB • HUAWEI-FWD-RES-TRAP-MIB • HUAWEI-FWD-PAF-TRAP-MIB • HUAWEI-GTL-MIB • HUAWEI-HWTACACS-MIB • HUAWEI-INFOCENTER-MIB • HUAWEI-IF-EXT-MIB • HUAWEI-IPFPM-MIB • HUAWEI-ISIS-CONF-MIB • HUAWEI-L2IF-MIB • HUAWEI-L2MAM-MIB • HUAWEI-L2MULTICAST-MIB • HUAWEI-L2VLAN-MIB • HUAWEI-L3VPN-EXT-MIB • HUAWEI-LDT-MIB • HUAWEI-LINE-MIB • HUAWEI-LLDP-MIB • HUAWEI-M-LAG-MIB • HUAWEI-MEMORY-MIB • HUAWEI-MFLP-MIB • HUAWEI-MIB • HUAWEI-MPLS-EXTEND-MIB • HUAWEI-MPLSLSR-EXT-MIB • HUAWEI-MSTP-MIB • HUAWEI-ND-MIB • HUAWEI-NETCONF-MIB

Category	MIB
Huawei-proprietary MIB	<ul style="list-style-type: none"> • HUAWEI-NETSTREAM-MIB • HUAWEI-NTP-TRAP-MIB • HUAWEI-NVO3-MIB • HUAWEI-OSPFV2-MIB • HUAWEI-OSPFV3-MIB • HUAWEI-OVSDB-MIB • HUAWEI-PERFMGMT-MIB • HUAWEI-PIM-STD-MIB • HUAWEI-PORT-MIB • HUAWEI-RIPv2-EXT-MIB • HUAWEI-RM-EXT-MIB • HUAWEI-SECURITY-MIB • HUAWEI-SMARTLINK-MIB • HUAWEI-SNMP-EXT-MIB • HUAWEI-SSH-MIB • HUAWEI-STACK-MIB • HUAWEI-SWITCH-L2MAM-EXT-MIB • HUAWEI-SYS-CLOCK-MIB • HUAWEI-SYS-MAN-MIB • HUAWEI-TASK-MIB • HUAWEI-TCP-MIB • HUAWEI-TRILL-CONF-MIB • HUAWEI-TRNG-MIB • HUAWEI-VBST-MIB • HUAWEI-VP-MIB • HUAWEI-VPLS-EXT-MIB • HUAWEI-VRRP-EXT-MIB • HUAWEI-XQOS-MIB

NOTE

For detailed information of MIB information, visit <http://support.huawei.com/hedex/hdx.do?docid=EDOC1100020548&lang=en&idPath=7919710%7C21782165%7C21782239%7C22318540%7C7597815> or contact your local

Standard Compliance

The following table lists the standards the CE 7800 complies with.

Standard Organization	Standard or Protocol
IETF	<ul style="list-style-type: none"> • RFC 768 User Datagram Protocol (UDP) • RFC 792 Internet Control Message Protocol (ICMP) • RFC 793 Transmission Control Protocol (TCP) • RFC 826 Ethernet Address Resolution Protocol (ARP) • RFC 854 Telnet Protocol Specification • RFC 951 Bootstrap Protocol (BOOTP) • RFC 959 File Transfer Protocol (FTP) • RFC 1058 Routing Information Protocol (RIP) • RFC 1112 Host extensions for IP multicasting • RFC 1157 A Simple Network Management Protocol (SNMP) • RFC 1256 ICMP Router Discovery • RFC 1305 Network Time Protocol Version 3 (NTP) • RFC 1349 Internet Protocol (IP) • RFC 1493 Definitions of Managed Objects for Bridges • RFC 1542 Clarifications and Extensions for the Bootstrap Protocol • RFC 1643 Ethernet Interface MIB • RFC 1757 Remote Network Monitoring (RMON) • RFC 1901 Introduction to Community-based SNMPv2 • RFC 1902-1907 SNMP v2 • RFC 1981 Path MTU Discovery for IP version 6 • RFC 2131 Dynamic Host Configuration Protocol (DHCP) • RFC 2328 OSPF Version 2 • RFC 2453 RIP Version 2 • RFC 2460 Internet Protocol, Version 6 Specification (IPv6) • RFC 2461 Neighbor Discovery for IP Version 6 (IPv6) • RFC 2462 IPv6 Stateless Address Auto configuration • RFC 2463 Internet Control Message Protocol for IPv6 (ICMPv6) • RFC 2474 Differentiated Services Field (DS Field) • RFC 2740 OSPF for IPv6 (OSPFv3) • RFC 2863 The Interfaces Group MIB • RFC 2597 Assured Forwarding PHB Group • RFC 2598 An Expedited Forwarding PHB • RFC 2571 SNMP Management Frameworks • RFC 2865 Remote Authentication Dial In User Service (RADIUS) • RFC 3046 DHCP Option82 • RFC 3376 Internet Group Management Protocol, Version 3 (IGMPv3) • RFC 3513 IP Version 6 Addressing Architecture • RFC 3579 RADIUS Support For EAP • RFC 4271 A Border Gateway Protocol 4 (BGP-4) • RFC 4760 Multiprotocol Extensions for BGP-4 • draft-grant-tacacs-02 TACACS+

Standard Organization	Standard or Protocol
IEEE	<ul style="list-style-type: none"> • IEEE 802.1D Media Access Control (MAC) Bridges • IEEE 802.1p Virtual Bridged Local Area Networks • IEEE 802.1Q Virtual Bridged Local Area Networks • IEEE 802.1ad Provider Bridges • IEEE 802.2 Logical Link Control • IEEE Std 802.3 CSMA/CD • IEEE Std 802.3ab 1000BASE-T specification • IEEE Std 802.3ad Aggregation of Multiple Link Segments • IEEE Std 802.3ae 10GE WEN/LAN Standard • IEEE Std 802.3x Full Duplex and flow control • IEEE Std 802.3z Gigabit Ethernet Standard • IEEE802.1ax/IEEE802.3ad Link Aggregation • IEEE 802.3ah Ethernet in the First Mile. • IEEE 802.1ag Connectivity Fault Management • IEEE 802.1ab Link Layer Discovery Protocol • IEEE 802.1D Spanning Tree Protocol • IEEE 802.1w Rapid Spanning Tree Protocol • IEEE 802.1s Multiple Spanning Tree Protocol • IEEE802.1x Port based network access control protocol • IEEE802.3af DTE Power via MDI • IEEE802.3at DTE Power via the MDI Enhancements
ITU	<ul style="list-style-type: none"> • ITU SG13 Y.17ethoam • ITU SG13 QoS control Ethernet-Based IP Access • ITU-T Y.1731 ETH OAM performance monitor
ISO	<ul style="list-style-type: none"> • ISO 10589 IS-IS Routing Protocol
MEF	<ul style="list-style-type: none"> • MEF 2 Requirements and Framework for Ethernet Service Protection • MEF 9 Abstract Test Suite for Ethernet Services at the UNI • MEF 10.2 Ethernet Services Attributes Phase 2 • MEF 11 UNI Requirements and Framework • MEF 13 UNI Type 1 Implementation Agreement • MEF 15 Requirements for Management of Metro Ethernet Phase 1 Network Elements • MEF 17 Service OAM Framework and Requirements • MEF 20 UNI Type 2 Implementation Agreement • MEF 23 Class of Service Phase 1 Implementation Agreement • Xmodem XMODEM/YMODEM Protocol Reference

NOTE

The listed standards and protocols are fully or partially supported by Huawei switches. For details, visit <https://e.huawei.com/ca/material/onLineView?MaterialID=821895aad0bd48e6aa079c06e82fb7f8> or contact your local Huawei sales office.

Optical transceivers and Cables

PartNumber	Product
40GE-QSFP+ Optical Transceivers	
QSFP-40G-SR-BD	40GBase-BD Optical Transceiver,QSFP+,40G,Multi-mode (850nm,0.1km,LC)
QSFP-40G-SDLC-PAM	40GBase-SDLC Optical Transceiver,QSFP+,40G,Multi-mode(850nm,PAM4,0.1km-OM3,0.15km-OM4,LC)
QSFP-40G-iSR4	40GBase-iSR4 Optical Transceiver,QSFP+,40G,Multi-mode (850nm,0.15km,MPO)(connecting to one QSFP+ or four SFP+)
QSFP-40G-eSR4	40GBase-eSR4 Optical Transceiver,QSFP+,40G,Multi-mode (850nm,0.3km,MPO)(connecting to one QSFP+ or four SFP+)
QSFP-40G-eSDLC-PAM	40GBase-eSDLC Optical Transceiver,QSFP+,40G,Multi-mode(850nm,PAM4,0.1km-OM3,0.3km-OM4,LC)
QSFP-40G-LX4	40GBase-LX4 Optical Transceiver,QSFP+,40GE,Single-mode(1310nm,2km,LC),Multi-mode(1310nm,0.15km,LC)
QSFP-40G-LR4-Lite	40GBase-LR4 Lite Optical Transceiver,QSFP+,40G,Single-mode Module(1310nm,2km,LC)
QSFP-40G-eSM4	40GBase-eSM4 Optical Transceiver,QSFP+,40G,Single-mode Module (1310nm,10km,MPO)(connecting to one QSFP+ or four SFP+)
QSFP-40G-LR4	40GBASE-LR4 optical transceiver, QSFP+, 40G, single-mode module (1310nm, 10km, LC)
QSFP-40G-ER4	40GBase-ER4 Optical Transceiver,QSFP+,40G,Single-mode Module (1310nm,40km,LC)
AOC High-Speed Cables	
QSFP-H40G-AOC10M	Optical transceiver,QSFP+,40G,(850nm,10m,AOC)
QSFP-4SFP10-AOC10M	Optical transceiver,QSFP+,40G,(850nm,10m,AOC)(Connect to four SFP+ Optical Transceiver)
Copper Cable	
QSFP-40G-CU1M	QSFP+, 40G, High Speed Direct-attach Cables, 1m, QSFP+38M, CC8P0.254B(S), QSFP+38M, Used indoor
QSFP-40G-CU3M	QSFP+, 40G, High Speed Direct-attach Cables, 3m, QSFP+38M, CC8P0.32B(S), QSFP+38M, Used indoor
QSFP-40G-CU5M	QSFP+, 40G, High Speed Direct-attach Cables, 5m, QSFP+38M, CC8P0.40B(S), QSFP+38M, Used indoor
QSFP-4SFP10G-CU1M	QSFP+, 4SFP+10G, High Speed Direct-attach Cables, 1m, QSFP+38M, CC8P0.254B(S), 4*SFP+20M, Used indoor
QSFP-4SFP10G-CU3M	QSFP+, 4SFP+10G, High Speed Direct-attach Cables, 3m, QSFP+38M, CC8P0.32B(S), 4*SFP+20M, Used indoor
QSFP-4SFP10G-CU5M	QSFP+, 4SFP+10G, High Speed Direct-attach Cables, 5m, QSFP+38M, CC8P0.4B(S), 4*SFP+20M, Used indoor

Ordering Information

Mainframe

CE7855-32Q-EI	CE7855-32Q-EI Switch (32-Port 40GE QSFP+, Without Fan and Power Module)
CE7855-EI-F-B00	CE7855-32Q-EI Switch (32-Port 40GE QSFP+, 2*AC Power Module, 2*FAN Box, Port-side Exhaust)
CE7855-EI-B-B00	CE7855-32Q-EI Switch (32-Port 40GE QSFP+, 2*AC Power Module, 2*FAN Box, Port-side Intake)

Fan box

Part Number	Product Description	Support Product
FAN-40HA-F	Fan box (HA, Front to Back, FAN panel side intake)	CE7855-32Q-EI
FAN-40HA-B	Fan box (HA, Back to Front, FAN panel side exhaust)	CE7855-32Q-EI

Power

Part Number	Product Description	Support Product
PAC-600WA-F	600W AC Power Module (Front to Back, Power panel side intake)	CE7855-32Q-EI
PAC-600WA-B	600W AC Power Module (Back to Front, Power panel side exhaust)	CE7855-32Q-EI

Software


CE-LIC-VXLAN	VXLAN function
CE78-LIC-FCF16	CloudEngine 7800 FCF 16 Ports license
CE78-LIC-FCFAL	CloudEngine 7800 FCF All Ports
CE78-LIC-NPV	CloudEngine 7800 FCOE NPV Function
CE78-LIC-TLM	CE7800 Telemetry Function
N1-CE78LIC-CFFD	N1-CloudFabric Foundation SW License for CloudEngine 7800
N1-CE78CFFD-SYS1Y	N1-CloudFabric Foundation SW License for CloudEngine 7800-SnS-1 Year
N1-CE78LIC-CFAD	N1-CloudFabric Advanced SW License for CloudEngine 7800
N1-CE78CFAD-SYS1Y	N1-CloudFabric Advanced SW License for CloudEngine 7800-SnS-1 Year

Networking and Application

Data Center Applications

On a typical data center network, CE12800/CE8800/CE7800 switches work as core switches, whereas CE6800 and CE5800 switches work as ToR switches and connect to the core switches using 100GE/40GE/10GE ports. These switches use fabric technology such as TRILL or VXLAN to establish a non-blocking large Layer 2 network, which allows large-scale VM migrations and flexible service deployments.

Note: TRILL and VXLAN can be also used on campus networks to support flexible service deployments in different service areas.




Campus Network Applications

The CE7800 can be used on a campus network. Its high-density, line-speed 40GE ports and high stacking capability can meet the ever-increasing demand for network bandwidth. CE7800 switches are cost-effective campus network switches, thanks to their extensive service features and innovative energy-saving technologies.

On a typical campus network, multiple CE12800/CE8800/CE7800 switches are virtualized into a logical core switch using CSS or iStack technology. Multiple CE6800 switches at the aggregation layer form a logical switch using iStack technology. CSS and iStack improve network reliability and simplify network management. At the access layer, CE5800 switches are virtualized with CloudFabric technology, such as SVF or M-LAG (vertical virtualization), to provide high-density line-rate ports.

Note: CSS, iStack, SVF, and M-LAG are also widely used in data centers to facilitate network management.



Copyright © Huawei Technologies Co., Ltd. 2018. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademark Notice



, HUAWEI, and  are trademarks or registered trademarks of Huawei Technologies Co., Ltd.

Other trademarks, product, service and company names mentioned are the property of their respective owners.

General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLOGIES CO.,LTD.
Huawei Industrial Base
Bantian Longgang
Shenzhen 518129,P.R.China
Tel: +86 755 28780808

www.huawei.com