

A Smarter Way for Your Broadband Life

EchoLife EG8245H, an intelligent routing-type ONT

Smart
service

Smart
interconnection

Smart O&M



O Device Parameters

| | |
|---------------------------|--|
| Dimensions (HxWxD) | 176 mm x 138.5 mm x 28 mm (without an external antenna) |
| Weight | About 280 g |
| Operating temperature | 0°C to +40°C |
| Operating humidity | 5% RH to 95% RH (non-condensing) |
| Power adapter input | 100 – 240 V AC, 50/60 Hz |
| System power supply | 11 – 14 V DC, 1.5 A |
| Static power consumption | 5.5 W |
| Maximum power consumption | 16.5 W |
| Ports | 2POTS + 4GE + Wi-Fi+ 1USB |
| Indicators | POWER/PON/LOS/LAN/TEL/USB /WLAN/WPS |

O Interface Parameters

| | |
|---------------|--|
| GPON Port | <ul style="list-style-type: none"> Class B+ Receiver sensitivity: -27 dBm Wavelengths: US 1310 nm, DS 1490 nm WBF Flexible mapping between GEM Port and TCONT GPON: consistent with the SN or password authentication defined in G.984.3 Bi-directional FEC SR-DBA and NSR-DBA |
| Ethernet Port | <ul style="list-style-type: none"> Ethernet port-based VLAN tags and tag removal 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission QinQ VLAN Limit on the number of learned MAC addresses MAC address learning |
| POTS Port | <ul style="list-style-type: none"> Maximum REN: 4 G.711A/μ, G.729a/b and G.722 encoding/decoding T.30/T.38/G.711 fax mode DTMF Emergency calls (with the SIP protocol) |
| USB Port | <ul style="list-style-type: none"> USB2.0 FTP-based network storage |
| WLAN | <ul style="list-style-type: none"> IEEE 802.11 b/g/n 2 x 2 MIMO Antenna gain: 5 dBi WMM Multiple SSIDs WPS Air interface rate: 2. 4G: 300 Mbit/s |

O Product Function

Smart interconnection

- Smart Wi-Fi coverage
- SIP/H.248 auto-negotiation
- Any port any service
- Parental control
- L2/L3 (IPv4) forwarding: 1G uplink, 2G downlink

Smart service

- Smart Wi-Fi sharing:
Portal/802.1x authentication
SoftGRE-based sharing
- Association of one account with two POTS ports

Smart O&M

- IPTV video quality diagnosis
- Variable-length OMCI messages
- Active/Passive rogue ONT detection and isolation
- Call emulation, and circuit test and loop-line test
- PPPoE/DHCP simulation testing
- WLAN emulation

Layer 3 Features

- PPPoE/Static IP/DHCP
- NAT/NAPT
- Port forwarding
- ALG, UPnP
- DDNS/DNS server/DNS client
- IPv6/IPv4 dual stack, and DS-Lite
- Static/Default routes
- Multiple services on one WAN port

Multicast

- IGMP v2/v3 proxy /snooping
- MLD v1/v2 snooping

QoS

- Ethernet port rate limitation
- 802.1p priority
- SP/WRR/SP+WRR
- Broadcast packet rate limitation

Security

- SPI firewall
- Filtering based on MAC/IP/URL addresses

Common O&M

- OMCI/Web UI/TR069
- Dual-system software backup and rollback

Power Saving

- Indicator power saving
- Scheduled Wi-Fi shutdown