

# EchoLife EG8247H5 Datasheet 04

EchoLife EG8247H5, an intelligent routing-type ONT

## **Overview**



### **Device Parameters**

Dimensions (H x W x D) (without external antenna and pads)	30 mm x 199 mm x 135 mm (without external antenna and pads)	System power supply	11–14 V DC, 1 A
Weight	About 300 g	Static power consumption	6 W
Operating temperature	0°C to 40°C	Maximum power consumption	12 W
Operating humidity	5% RH to 95% RH (non- condensing)	NNI	GPON
Power adapter input	100-240 V AC, 50/60 Hz	UNI	2POTS+4GE+1CATV+2.4G Wi-Fi+1USB
Indicators	Power/PON/LOS/LAN/TEL/U SB/WLAN/WPS/CATV	Optical Connector	SC/APC

# **Interface Parameters**

GPON port	POTS port	
<ul> <li>Class B+</li> <li>Receiver sensitivity: -27dBm ~ -29dBm</li> <li>Overload optical power: -8 dBm</li> <li>Wavelengths: US 1310nm, DS 1490nm</li> <li>Wavelength blocking filter (WBF) of G.984.5</li> <li>Flexible mapping between GEM Port and TCONT</li> <li>GPON: consistent with the SN or password authentication defined in G.984.3</li> <li>Bi-directional FEC</li> <li>SR-DBA and NSR-DBA</li> <li>Type B (single-homing&amp;dual-homing)</li> </ul>	<ul> <li>Maximum REN: 4</li> <li>G.711A/µ, G.729a/b, and G.722 encoding/decoding</li> <li>T.30/T.38/G.711 fax mode</li> <li>DTMF</li> <li>Emergency calls (with the SIP protocol)</li> </ul>	
Ethernet port	USB port	
<ul> <li>Ethernet port-based VLAN tags and tag removal</li> <li>1:1 VLAN, N:1 VLAN, or VLAN transparent transmission</li> <li>QinQ VLAN</li> <li>Limit on the number of learned MAC addresses</li> <li>MAC address learning</li> <li>Auto-adaptive 10 Mbit/s, 100 Mbit/s or 1000 Mbit/s</li> </ul>	• USB2.0	
CATV port	WLAN	
<ul> <li>Frequency Range 54 MHz to 870 MHz</li> <li>Output resistance 75 ohms</li> <li>Received average optical power: -8dBm to +2dBm</li> <li>RF output power: ≥17dBmV/Ch         (With RF source analog channel power input = 20dBmV/ch, and 40 analog / 63 digital channels (4.3% OMI analog, 2.15 % digital))     </li> </ul>	<ul> <li>IEEE 802.11 b/g/n</li> <li>2 x 2 MIMO</li> <li>Antenna gain: 5 dBi</li> <li>WMM</li> <li>Multiple SSIDs</li> <li>WPS</li> <li>Air interface rate: 300 Mbit/s</li> </ul>	

# **Product Function**

Smart interconnection	Smart O&M	Layer 3 features	Security
<ul> <li>Smart Wi-Fi coverage</li> <li>SIP/H.248 autonegotiation</li> <li>Any port any service</li> <li>Parental control</li> </ul>	<ul> <li>IPTV video quality diagnosis</li> <li>eMDI</li> <li>Rogue ONT detection and isolation from the OLT</li> <li>Call emulation, and circuit test and loop-line test</li> <li>PPPoE/DHCP simulation testing</li> </ul>	<ul> <li>PPPoE/Static IP/DHCP</li> <li>NAT/NAPT</li> <li>Port forwarding</li> <li>ALG, UPnP</li> <li>DDNS/DNS server/DNS client</li> <li>IPv6/IPv4 dual stack, and DS-Lite</li> <li>Static/Default routes</li> <li>Multiple services on one WAN port</li> </ul>	<ul> <li>SPI firewall</li> <li>Filtering based on MAC/IP/URL addresses</li> <li>Common O&amp;M</li> <li>OMCI/Web UI/TR069</li> <li>Variable-length OMCI messages</li> <li>Dual-system software backup and rollback</li> </ul>

	WLAN emulation		
Multicast	Smart service	Power saving	QoS
<ul> <li>IGMP v2/v3 proxy/snooping</li> <li>MLD v1/v2 snooping</li> </ul>	<ul> <li>Scheduled Wi-Fi shutdown</li> <li>Smart Wi-Fi sharing:         Portal/802.1x authentication         SoftGRE-based sharing     </li> <li>Association of one account with two POTS ports</li> </ul>	<ul><li>Indicator power saving</li><li>COC V5</li></ul>	<ul> <li>Ethernet port rate limitation</li> <li>802.1p priority</li> <li>SP/WRR/SP+WRR</li> <li>Broadcast packet rate limitation</li> </ul>

### Copyright © Huawei Technologies Co., Ltd. 2020. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

### **Trademarks and Permissions**

WHUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

### Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

### Huawei Technologies Co., Ltd.

Address:Huawei Industrial Base Bantian, Longgang Shenzhen 518129 People's Republic of China

Website:http://www.huawei.com