

A Smarter Way for Your Broadband Life

Huawei HG8245D, an intelligent routing-type ONT

Smart
service

Smart
interconnection

Smart O&M



○ Device Parameters

Dimensions (HxWxD)	(235 x 195 x 30)mm
Weight	about 500g
Operating temperature	0°C to +40°C
Operating humidity	5%RH to 95%RH (non-condensing)
Power adapter input	100–240V AC, 50–60Hz
System power supply	11–14V DC, 2 A
Static power consumption	12W
Maximum power consumption	21W
Ports	2POTS+4GE+2.4G/5G Wi-Fi +USB

○ Interface Parameters

GPON Port	• Class B+ • Receiver sensitivity: -27dBm • Wavelengths: US 1310nm, DS 1490nm • WBF • Flexible mapping between GEM Port and TCONT • GPON: consistent with the SN or password authentication defined in G.984.3 • Bi-directional FEC • SR-DBA and NSR-DBA
Ethernet Port	• Ethernet port-based VLAN tags and tag removal • 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission • QinQ VLAN • Limit on the number of learned MAC addresses • MAC address learning
POTS Port	• Maximum REN: 4 • G.711A/μ, G.729a/b, and G.722 encoding/decoding • T.30/T.38/G.711 fax mode • DTMF • Emergency calls (with the SIP protocol)
USB Port	• USB2.0 • FTP-based network storage • File/Print sharing based on SAMBA • DLNA DMS/UPnP AV (media server)
WLAN	• IEEE 802.11 b/g/n(2.4G) • IEEE 802.11 a/n(5G) • 3 × 3 MIMO • Antenna gain: 2 dBi • WMM • Multiple SSIDs • WPS • 2.4G/5G concurrent

○ Product Function

Smart interconnection

- Smart Wi-Fi coverage (V300R015C10)
- SIP/H.248 auto-negotiation
- Any port any service
- Parental control (V300R015C00)
- L2/L3 forwarding: 1G uplink, 2G downlink

Smart service

- Smart Wi-Fi sharing:
 - Portal/802.1x authentication (V300R015C10)
 - SoftGRE-based sharing (V300R015C10)
- Association of one account with two POTS ports

Smart O&M

- IPTV video quality diagnosis (V300R015C10)
- Variable-length OMCI messages
- Active/Passive rogue ONT detection and isolation
- Call emulation, and circuit test and loop-line test
- PPPoE/DHCP simulation testing
- WLAN emulation

Layer 3 Features

- PPPoE/Static IP/DHCP
- NAT/NAPT
- Port forwarding
- ALG, UPnP
- DDNS/DNS server/DNS client
- IPv6/IPv4 dual stack, and DS-Lite
- Static/Default routes
- Multiple services on one WAN port

Multicast

- IGMP v2/v3 proxy (V300R015C00) /snooping
- MLD v1/v2 snooping
- Multicast services through Wi-Fi

QoS

- Ethernet port rate limitation
- 802.1p priority
- SP/WRR/SP+WRR
- Broadcast packet rate limitation

Security

- SPI firewall
- Filtering based on MAC/IP/URL addresses

Common O&M

- OMCI/Web UI/TR069
- Dual-system software backup and rollback

Power Saving

- Dynamic power saving
- Indicator power saving
- Scheduled Wi-Fi shutdown (V300R015C00)