

A Smarter Way for Your Broadband Life

Huawei HG8247H, an intelligent routing-type ONT

Smart
service

Smart
interconnection

Smart O&M



O Device Parameters

| | |
|---------------------------|--|
| Dimensions (L x W x H) | 220 mm x 160 mm x 32 mm (without an external antenna) |
| Weight | About 400 g |
| Operating temperature | 0°C to 40°C |
| Operating humidity | 5% RH to 95% RH (non-condensing) |
| Power adapter input | 100–240 V AC, 50/60 Hz |
| System power supply | 11–14 V DC, 2 A |
| Static power consumption | 7.5 W |
| Maximum power consumption | 18 W |
| Ports | 2POTS + 4GE + CATV + Wi-Fi + USB |
| Indicators | POWER/PON/LOS/LAN/TEL/USB /WLAN/WPS/CATV |

O Interface Parameters

| | |
|----------------------|---|
| GPON Port | <ul style="list-style-type: none">Class B+Receiver sensitivity: -27 dBmWavelengths: US 1310 nm, DS 1490 nmWBFFlexible mapping between GEM Port and TCONTGPON: consistent with the SN or password authentication defined in G.984.3Bi-directional FECSR-DBA |
| Ethernet Port | <ul style="list-style-type: none">Ethernet port-based VLAN tags and tag removal1:1 VLAN, N:1 VLAN, or VLAN transparent transmissionQinQ VLANLimit on the number of learned MAC addressesMAC address learning |
| CATV Port | <ul style="list-style-type: none">Bandwidth 54-870 MHzOutput resistance 75 ohms |
| POTS Port | <ul style="list-style-type: none">Maximum REN: 4G.711A/μ, G.729a/b, and G.722 encoding/decodingT.30/T.38/G.711 fax modeDTMFEmergency calls (with the SIP protocol) |
| USB Port | <ul style="list-style-type: none">USB2.0FTP-based network storage |
| WLAN | <ul style="list-style-type: none">IEEE 802.11 b/g/n2 x 2 MIMOAntenna gain: 2 dBiWMMMultiple SSIDsWPSAir interface rate: 300 Mbps |

O Product Function

Smart interconnection

- Smart Wi-Fi coverage (V300R015C10)
- SIP/H.248 auto-negotiation
- Any port any service
- Parental control (V300R015C10)
- L2/L3(IPv4) forwarding: 1G uplink, 2G downlink

Smart service

- Smart Wi-Fi sharing:
Portal/802.1x authentication (V300R015C10)
SoftGRE-based sharing (V300R015C10)
- Association of one account with two POTS ports

Smart O&M

- Variable-length OMCI messages
- Active/Passive rogue ONT detection and isolation
- Call emulation, and circuit test and loop-line test
- PPPoE/DHCP simulation testing
- WLAN emulation

Layer 3 Features

- PPPoE/Static IP/DHCP
- NAT/NAPT
- Port forwarding
- ALG, UPnP
- DDNS/DNS server/DNS client
- IPv6/IPv4 dual stack
- Static/Default routes
- Multiple services on one WAN port

Multicast

- IGMP v2/v3 proxy(V300R015C00) /snooping
- MLD v1/v2 snooping
- Multicast services through Wi-Fi

QoS

- Ethernet port rate limitation
- 802.1p priority
- SP/WRR/SP+WRR
- Broadcast packet rate limitation

Security

- SPI firewall
- Filtering based on MAC/IP/URL addresses

Common O&M

- OMCI/Web UI/TR069
- Dual-system software backup and rollback

Power Saving

- Indicator power saving
- Scheduled Wi-Fi shutdown (V300R015C00)