OptiXstar P670E Datasheet

Enterprise-Level Routing Gateway ONU   Date: 2023-07-07

Product Overview

Huawei OptiXstar P670E product is a panel-type ONU which can be easily installed in 86-type electrician boxes in enterprise campus scenarios. It provides one GPON port in the upstream direction, and provides one GE Ethernet port and POTS port on the user side. With excellent forwarding capabilities, the ONU can ensure user experience in voice, data, and HD video services, providing ideal solutions and future-oriented service support capabilities for enterprise campuses.

Product Highlights

- Compact design, plug-and-play, flexible and easy to install
- 802.1x and IPv6/IPv4 firewalls to ensure device access security and network security

- High reliability with type B dual-homing service protection.

Technical Specifications

Dimensions	Panel: 86 mm x 86 mm x 9.5 mm Internal module depth: 35 mm	UNI	GPON
Weight	About 150 g	NNI	1GE+1POTS
Operating temperature	-5°C to +40°C	Surge protection specifications	GE: common mode 2.5 kV; POTS:common mode 2.5 kV. AC power: common mode 6 kV; differential mode 4 kV.
Operating humidity	5%RH to 95%RH (non-condensing)	Static power consumption	2.5W
Power adapter input	AC input: 100–240 V AC, 50/60 Hz	Maximum power consumption	5.8W
		Installation mode	Indoor 86-box installation

Port Parameters

GPON	GE	POTS
- Port type: SC/UPC - Complying with ITU-T G.984.2, Class B+ - Receiver sensitivity: -27dBm ~ -29dBm; - Overload optical power: -8dBm; - Transmission rate: upstream 1.244 Gbit/s, downstream 2.488 Gbit/s - Type B single-homing - Type B dual-homing (supported in Layer 2 forwarding)	- Port type:RJ-45 - Auto ports speed(10/100/1000 Mbit/s) - Half-duplex/full-duplex mode negotiation and configuration - Auto-MDI/MDIX - Configuration of the number of MAC addresses learned - VLAN transparent transmission/VLAN filtering	- Maximum REN: 4 - G.711A/µ, G.729a/b, and G.722 encoding/decoding - T.30/T.38/G.711 fax mode - DTMF - Emergency calls (with the SIP protocol)

Function List

Automatic Service Provisioning	Smart O&M	Multicast
- Authentication exemption - XML/OMCI/TR069	- Variable-length OMCI messages - Rogue ONT detection and self-regulation - Ring network detection/PPPoE/DHCP simulation testing	- IGMP v2/v3 snooping - MLDv1/MLDv2 snooping - Quickly leave - Downstream multicast VLAN translation/transparent transmission/stripping - IGMP/MLD packet rate limitation
QoS	Common O&M	Security

• Ethernet port rate limitation • 802.1p priority • SP/WRR/SP+WRR • Broadcast packet rate limitation • Flow mapping based on VLAN, 802.1p, Ethernet port, or any combination of VLAN, 802.1p, and Ethernet port	• OMCI/Web UI • Software dual backup and rollback • 802.1ag Ethernet OAM • Optical link measurement and diagnosis • Loop detection	• MAC filtering
		Power saving
		• Indicator power saving • Power consumption reduction of idle components in power-saving state

Huawei Technologies Co., Ltd.

Address:Huawei Industrial Base Bantian, Longgang Shenzhen 518129 People's Republic of China

Website:www.huawei.com