


Huawei OptiXstar P802E Datasheet

Enterprise-Level Routing Gateway ONU

Date: 2024-05-16

Product Overview

The OptiXstar P802E is an ONU designed for scenarios such as enterprise campus and video backhaul. It supports XGS-PON uplink access and provides 4 GE ports to provide high-quality voice, data, and HD video services.



Product Highlights

- Compact design, plug and play, flexible and easy to install.
- 802.1x and IPv6/IPv4 firewalls ensure device access security and network security.
- Supports XGS-PON uplink access.
- Supports -40° C to +55° C wide temperature range with strong environment adaptability.
- Features high reliability, 6 kV surge protection in common mode, and type B dual-homing service protection.

Technical Specifications

Dimensions (WxDxH)	160mm x 110mm x 30mm(Without floor mat)	NNI	XGS-PON
Weight	About 480 g	UNI	4*GE
Operating temperature	-40°C to +55°C	Static power consumption	4.5 W
Operating humidity	5%RH to 95%RH (non-condensing)	Maximum power consumption	6 W

Power adapter input	100V to 240V AC, 50/60Hz	Surge protection specifications	GE: common mode 6 kV; differential mode 1.5 kV. AC power : common mode 6 kV; differential mode 6 kV
System power supply	11V to 14V (typical 12 V), 1A	Installation mode	Support outdoor network box installation and indoor desktop installation, wall mounting, or network box installation.

Port Parameters


SFP	GE
<ul style="list-style-type: none"> Support XGS-PON optical module Port type: SC/UPC Class N1/N2; Receiver sensitivity: -28dBm; Overload optical power: -9dBm; Transmission rate: upstream 9.953 Gbit/s, downstream 9.953 Gbit/s Type B single-homing Type B dual-homing (supported in Layer 2 forwarding) 	<ul style="list-style-type: none"> Port type: RJ-45 Auto ports speed (10/100/1000 Mbit/s) Auto-MDI/MDIX Configuration of the number of MAC addresses learned VLAN transparent transmission/VLAN filtering

Function List

Automatic Service Provisioning	Smart O&M	Layer 3 Features	Security
<ul style="list-style-type: none"> Authentication exemption XML/OMCI/TR069 	<ul style="list-style-type: none"> XML/Web UI Rogue ONT detection and self-regulation Ring network detection/PPPoE/DHCP simulation testing 	<ul style="list-style-type: none"> Default/Static/Policy/Service routes VLAN binding ALG/UPnP/ARP DDNS/DMZ/DNS/NAPT PPPoE/Static IP/DHCP Port mapping/Port trigger IPv6 	<ul style="list-style-type: none"> 802.1x IPv6/IPv4 firewalls Filtering based on MAC/IP/URL DoS/ARP anti-attacks Static MAC address binding Device access control Web session number restriction
Multicast	QoS	Layer 2 Management	
<ul style="list-style-type: none"> IGMP v2/v3 snooping Dynamic controllable multicast IGMP proxy MLDv1/MLDv2 snooping 	<ul style="list-style-type: none"> Ethernet port rate limitation 802.1p priority SP/WRR/SP+WRR 	<ul style="list-style-type: none"> DHCP Option82 PITP BPDU transparent transmission LLDP/LLDP-MED 	

Power Adapter Specifications


Specification	Description
---------------	-------------

Specification	Description
Appearance	
Dimensions	90 mm (L) × 46 mm (W) × 30 mm (H)
Power supply specifications	Rated input voltage: 100 V to 240 V AC, 50/60 Hz Rated output voltage/current: 12 V DC/1 A Input/output connector type: C8 / $\phi 2.1 \times \phi 5.5 \times 9.5$ mm, "H" plug DC head semi-insulated head
Power	12 W
Installation mode	Desktop
Operating temperature	–40°C to +55°C
Output power cable	Specifications: 24AWG Cable length: 1.5m

Copyright © Huawei Technologies Co., Ltd. 2024. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

 HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base Bantian,
Longgang Shenzhen 518129 People's
Republic of China

Website: www.huawei.com