

Huawei OptiXstar P803E-E Datasheet

Enterprise-Level Routing Gateway ONU

Date: 2024-02-06

Product Overview

The Huawei OptiXstar P803E-E is an ONU designed for scenarios such as enterprise campus and video backhaul. It provides 8 GE ports to provide high-quality voice, data, and HD video services.



Product Highlights

- 802.1x and IPv6/IPv4 firewalls ensure device access security and network security.
- Supports XGS-PON uplink access.
- Supports -40°C to $+55^{\circ}\text{C}$ wide temperature range with strong environment adaptability.
- Features high reliability, and supports type B and type C service protection.
- Centralized management on eSight.
- Multi-network convergence, supporting ONU port-level hard-isolated. Different ports of an ONU can be securely connected to multiple networks through the hard-isolated technology.

Technical Specifications

Dimensions (WxDxH)	220mm x 150mm x 35mm (Without floor mat)	UNI	8*GE GE1 can be used as an upstream port.
Operating temperature	-40°C to $+55^{\circ}\text{C}$	NNI	2*XGS-PON (1*BOB+1*SFP)
Operating humidity	5%RH to 95%RH (non-condensing)	Surge protection specifications	GE: common mode 6 kV; differential mode 1.5 kV. AC power: common mode 6 kV;

			differential mode 6 kV.
Power adapter input	100V to 240V AC, 50/60Hz	Installation mode	Can be placed horizontally on a desk, installed under a desk, mounted on a wall, or installed in a cabinet or network box.
System power supply	12V DC, 1A	Weight	About 1.2kg
Static power consumption	6 W	Maximum power consumption	8 W

Port Parameters

XGS-PON	GE
<ul style="list-style-type: none"> XGS-PON optical module, port type: SC/UPC XGS-PON <ul style="list-style-type: none"> Class N1/N2 Receiver sensitivity: -28dBm Overload optical power: -9dBm Transmission rate: upstream 9.953 Gbit/s, downstream 9.953 Gbit/s Type B single-homing Type B dual-homing (supported in Layer 2 forwarding) Type C protection 	<ul style="list-style-type: none"> Port type: RJ-45 Auto ports speed (10/100/1000 Mbit/s) Auto-MDI/MDIX Configuration of the number of MAC addresses learned VLAN transparent transmission/VLAN filtering


Function List

Automatic Service Provisioning	Smart O&M	Layer 3 Features	Security
<ul style="list-style-type: none"> Authentication exemption XML/OMCI/TR069 	<ul style="list-style-type: none"> XML/Web UI Rogue ONT detection and self-regulation Ring network detection/PPPoE/DHCP simulation testing 	<ul style="list-style-type: none"> Default/Static/Policy/Service routes VLAN binding ALG/UPnP/ARP DDNS/DMZ/DNS/NAPT PPPoE/Static IP/DHCP Port mapping/Port trigger IPv6 	<ul style="list-style-type: none"> 802.1x IPv6/IPv4 firewalls Filtering based on MAC/IP/URL DoS/ARP anti-attacks Static MAC address binding Device access control Web session number restriction ONU Port-Level Hard-Isolated (V500R022C00 and later versions)
Multicast	QoS	Layer 2 Management	
<ul style="list-style-type: none"> IGMP v2/v3 snooping Dynamic controllable multicast IGMP proxy MLDv1/MLDv2 snooping 	<ul style="list-style-type: none"> Ethernet port rate limitation 802.1p priority SP/WRR/SP+WRR 	<ul style="list-style-type: none"> DHCP Option82 PITP BPDU transparent transmission LLDP/LLDP-MED 	

Power Adapter Specifications

NOTE


This power adapter is delivered with the device.

Specification	Power Adapter
Appearance	
Dimensions	96 mm (length) x 44 mm (width) x 30 mm (height)
Power supply specifications	Input voltage: 100–240 V AC, 50 Hz/60 Hz Rated output voltage/current: 12V DC/1A Input/Output connector type: C8 2Pin/DC straight audio plug 4.0*1.7
Power	12 W
Weight	About 0.11Kg
Installation mode	Desktop
Operating temperature	–40°C to +55°C
Power cable	Specifications: 2468 22AWG Cable length: 1.5m

Copyright © Huawei Technologies Co., Ltd. 2024. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

 HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base Bantian,
Longgang Shenzhen 518129 People's
Republic of China

Website: www.huawei.com